## **AMENDMENTS TO THE CLAIMS**

Docket No.: 2565-0300PUS1

- 1. (Canceled)
- 2. (Currently Amended) The A mobile station of claim 1-which communicates with a base station by using a direct sequence system, comprising:

a special call part configured to request initiation of a special call;

a mobile station side transmission part configured to, in response to a request from the special call part, generate a special radio wave signal of high power spectrum density and transmit it to the base station; and

\_\_\_\_a spread modulation part <u>configured</u> to perform spread modulation of an information signal, wherein

the mobile station side transmission part generates the special radio wave signal <u>to be</u> of high power spectrum density by bypassing the spread modulation part.

3. (Currently Amended) The A mobile station of claim 1 which communicates with a base station by using a direct sequence system, comprising:

a special call part configured to request initiation of a special call; and

a mobile station side transmission part configured to, in response to a request from the special call part, generate a special radio wave signal of high power spectrum density and transmit it to the base station, wherein

the mobile station side transmission part includes a special code generation part to generate a special code of a direct-current component, and a spread modulation part to perform spread modulation of an information signal by using the special code generated by the special code generation part, and

the mobile station side transmission part generates the special radio wave signal of high power spectrum density by performing spread modulation of the information signal by using the special code of the direct-current component. 4. (Currently Amended) The mobile station of claim 2 or 3-further including a communication control part to restrict a bit rate of the information signal to be low when the mobile station side transmission part generates the special radio wave signal, in order to increase power spectrum density of the special radio wave signal by restricting the bit rate to be low.

Docket No.: 2565-0300PUS1

- 5. (Currently Amended) The mobile station of claim 2, 1, wherein the mobile station side transmission part performs communication by using the special radio wave signal until a session with the base station is established.
- 6. (Currently Amended) The A mobile station which communicates with a base station by using a direct sequence system, comprising: of claim 1

a special call part configured to request initiation of a special call; and

a mobile station side transmission part configured to, in response to the request from the special call part, generate a special radio wave signal of high power spectrum density and transmit the special radio wave signal to the base station, wherein

the mobile station side transmission part generates the special radio wave signal of same power as power used in the direct sequence system, and of a narrower band than a band used in the direct sequence system.

7. (Currently Amended) A communication control method for performed by a mobile station side to communicate with a base station by using a direct sequence system, comprising:

requesting to initiate initiation of a special call; and

in response to the request for initiation of ing to initiate the special call, generating a special radio wave signal of high power spectrum density and transmitting it the special radio wave signal to the base station, wherein

the special radio wave signal is generated of same power as power used in the direct sequence system, and of a narrower band than a band used in the direct sequence system.

8. (Currently Amended) A base station which communicates with a plurality of mobile stations by using <u>a</u> direct sequence system, comprising:

Docket No.: 2565-0300PUS1

a base station side reception part <u>configured</u> to receive a special radio wave signal of high power spectrum density from the plurality of mobile stations, the special radio wave signal being generated of same power as power used in the direct sequence system, and of a narrower band than a band used in the direct sequence system;

a detection part <u>configured</u> to detect whether the base station side reception part received the special radio wave signal; and

a base station side transmission part <u>configured</u> to transmit an assignment signal for assigning a channel to a mobile station which had transmitted the special radio wave signal detected by the detection part.

## 9-10. (Canceled)

11. (Currently Amended) A communication system where a base station and a plurality of mobile stations communicate using <u>a</u> direct sequence system, comprising: the plurality of mobile stations, each including

\_\_\_\_\_a special call part <u>configured</u> to request <u>to initiate initiation of</u> a special call, and \_\_\_\_\_a mobile station side transmission part <u>configured to</u>, in response to a request from the special call part, to generate a special radio wave signal of high power spectrum density and transmit it to the base station, <u>wherein the mobile station side transmission part generates the special radio wave signal of same power as power used in the direct sequence system, and of a <u>narrower band than a band used in the direct sequence system</u>; and</u>

the base station including:

\_\_\_\_a base station side reception part <u>configured</u> to receive the special radio wave signal of high power spectrum density from the plurality of mobile stations,

\_\_\_\_a detection part <u>configured</u> to detect whether the base station side reception part received the special radio wave signal, and

\_\_\_\_a base station side transmission part <u>configured</u> to transmit an assignment signal for assigning a channel to a mobile station which had transmitted the special radio wave signal detected by the detection part.

Docket No.: 2565-0300PUS1

12. (Currently Amended) A <u>computer-readable medium on which is embodied a communication</u> control program\_, having computer executable <u>instructions processing</u>, for <u>causing</u> a mobile station side to communicate with a base station by using <u>a direct sequence system</u>, comprising <u>instructions</u> for:

processing of requesting to initiate initiation of a special call; and

in response to the <u>request for initiation of requesting to initiate</u> the special call, <del>processing</del> of generating a special radio wave signal of high power spectrum density and transmitting it to the base station, <u>wherein</u>

the special radio wave signal is generated of same power as power used in the direct sequence system, and of a narrower band than a band used in the direct sequence system.

13. (Currently Amended) A <u>computer-readable medium on which is embodied a communication</u> control program\_, having computer executable <u>instructions processing</u>, for <u>causing</u> a base station side to communicate with a plurality of mobile stations by using <u>a direct sequence system</u>, comprising <u>instructions for</u>:

processing of receiving a special radio wave signal of high power spectrum density from the plurality of mobile stations, the special radio wave signal being generated of same power as power used in the direct sequence system, and of a narrower band than a band used in the direct sequence system;

processing of detecting whether the special radio wave signal was received; and processing of transmitting an assignment signal for assigning a channel to a mobile station which had transmitted the special radio wave signal detected.

14. (New) The mobile station of claim 3, further including a communication control part configured to restrict a bit rate of the information signal to be low when the mobile station side

Docket No.: 2565-0300PUS1

transmission part generates the special radio wave signal, in order to increase power spectrum density of the special radio wave signal by restricting the bit rate to be low.

## 15. (New) The mobile station of claim 3, wherein

the mobile station side transmission part performs communication by using the special radio wave signal until a session with the base station is established.

## 16. (New) The mobile station of claim 6, wherein

the mobile station side transmission part performs communication by using the special radio wave signal until a session with the base station is established.